



RoHS Compliant

Features

- Compact and low profile (5×3.2×1.2mm)
- Surface mount type suitable for auto pick-and-place
- Reflow soldering compatible
- CMOS, TTL IC direct drive is possible
- With tri-state function
- Supply voltage V_{CC}=3.3/ 5.0V available

Frequency Tolerance (Overall)

Freq. Tol. Code	Freq. Tol. × 10 ⁻⁶	Operating Temperature Range (°C)	Note
1	±100	-10 to +70 (standard)	1.8 to 50MHz
0	± 50		1.8 to 32MHz
S	± 30		1.8 to 32MHz

How to Order

KC5032D 25.0000 C 3 1 B 00
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5=5.0V, 3=3.3V
- ⑤ Frequency Tolerance (See table at left)
- ⑥ Symmetry/ INH Function
 A: 40/ 60%, Disable
 B: 40/ 60%, Stand-by
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Symmetry/ INH Function

Freq. (MHz)	Code	
	KC5032D-C5	KC5032D-C3
1.8 to 50	A	B


Specifications

Item	Symbol	Conditions		Units
		KC5032Dxx.xxxxC5xA00 (FXO-61F2)	KC5032Dxx.xxxxC3xB00 (FXO-61FL2)	
Output Frequency Range	f _o	1.8 to 50		MHz
Frequency Tolerance (Overall)	f _{tol}	±30 (to 32MHz)		×10 ⁻⁶
		±50 (to 32MHz)		
		±100 (to 50MHz)		
Storage Temperature Range	T _{stg}	-40 to +85		°C
Operating Temperature Range	T _{use}	-10 to +70		°C
Max. Supply Voltage	—	7 max.		V
Supply Voltage	V _{CC}	5±0.5	3.3±0.3	V
Current Consumption	I _{CC}	25 max.	18 max. (1.8 to 39.9MHz)	mA
			25 max. (40 to 50MHz)	
Stand-by/ Disable Current	I _{std}	10 max.		µA
Symmetry	SYM	40 to 60@50%V _{CC}		%
Rise/ Fall Time	t _r / t _f	10 max.		ns
Low Level Output Voltage	V _{OL}	10% V _{CC} max.		V
High Level Output Voltage	V _{OH}	90% V _{CC} min.		V
CMOS Load	L _{CMOS}	15 max.	20 max.	pF
Input Voltage Range	V _{IN}	0 to V _{CC}		V
Low Level Input Voltage	V _{IL}	0.8 max.		V
High Level Input Voltage	V _{IH}	2.2 min.		V
Disable Time	t _{dis}	150 max.		ns
Enable Time	t _{ena}	5 max.		ms
Start-up Time	t _{str}	10 max.		ms

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
 Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

