



RoHS Compliant

Features

- Analog signal processing temperature compensated crystal oscillator
- Small package & Lower noises

Standard frequency

- 14.31818MHz
- 17.734475MHz
- 28.63636MHz

How to Order

TV 14.3181800 M 04017AH
 ① ② ③ ④

- ① Function
VC-TCXO → TV
- ② Output Frequency
- ③ Frequency Unit
M→MHz
- ④ Individual Specification

Table 1

Model	Output waveform	Individual Specification
VC-TCXO-155	clipped sinusoidal wave	04017AH
VC-TCXO-155CB	CMOS	05002AH

Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Frequency Range	fo	—	10	30	MHz
Frequency tolerance	fo-Tc	vs Temperature	-1.0	+1.0	$\times 10^{-6}$
	fo-Vcc	vs Voltage	-0.2	+0.2	$\times 10^{-6}$
Storage Temperature Range	T _{stg}	—	-40	+85	°C
Operating Temperature Range	T _{use}	—	-10	+60	°C
Supply Voltage	Vcc	—	4.75	5.25	V
Current consumption	Icc	VC-TCXO-155	—	3	mA
		VC-TCXO-155CB	—	20	mA
Frequency Aging	f _{age}	1 year	1.0	1.0	$\times 10^{-6}$
Frequency Adjustment Range	f _{adjust}	Internal Trimmer	-3.0	+3.0	$\times 10^{-6}$
Frequency Control Range	f _{cont}	—	-10	+10	$\times 10^{-6}$
Frequency Deviation	VC	—	0.5	4.5	V
Load	Load _R	VC-TCXO-155	100000	100000	ohm
	Load _C	VC-TCXO-155	10	10	pF
Output Level	Output Level	VC-TCXO-155	-10	—	dBm
CMOS Load	L _{CMOS}	VC-TCXO-155CB	—	15	pF
Low Level Output Voltage	V _{OL}	VC-TCXO-155CB	—	90% Vcc	V
High Level Output Voltage	V _{OH}	VC-TCXO-155CB	10% Vcc	—	V
Symmetry	Symmetry	VC-TCXO-155CB, @50% Vcc	40	60	%

Dimensions

(Unit: mm)

